

TIOMOS ŠARKA ZA UGAO 30°



KARAKTERISTIKE:


- Za 30° kosi korpus
- Ugao otvaranja 110°
- Jednostavno podešavanje dubine pomoću navoja
- 3-D podešavanje uz odgovarajuću montažnu pločicu
- Minimalne dimenzije fuga

Šifra	Opis artikla
F028138529	ŠARKA TIOMOS 30° SA UBLAŽIVAČEM-RAVNA TS
F045138467	ŠARKA TIOMOS 30° BEZ UBLAŽIVAČA-RAVNA T



TEHNIČKO UPUTSTVO ZA MONTAŽU I UGRADNJU

UZORCI BUŠENJA


Pričvršćivanje vijkom







Kombinovani uzorak bušenja za impresso



Obična pločica



Ravna pločica



	Udaljenost čašice					
	3	4	5	6	7	
Preklop vrata	21.0				0	
	19.5			0		
	18.5			0	2	
	17.5		0		2	3
	16.5	0				3.5
	16.0			2	3	
	15.5				3.5	
	15.0		2	3		
	14.5			3.5		
	14.0	2	3			
	13.5		3.5			
	13.0	3				
	12.5	3.5			6	
11.5			6			
10.5		6				
	Visina montažne pločice					

	Udaljenost čašice						
	3	4	5	6	7		
Preklop vrata	24.0	1.0	1.0	1.0	1.2	2.1	
	22.0	1.0	1.0	1.0	1.0	1.5	
	21.0	1.0	1.0	1.0	1.0	1.2	
	20.0	1.0	1.0	1.0	1.0	1.0	
	19.0	1.0	1.0	1.0	1.0	1.0	
	18.0	1.0	1.0	1.0	1.0	1.0	
	17.0	1.0	1.0	1.0	1.0	1.0	
	16.0	1.0	1.0	1.0	1.0	1.0	
	Minimalni razmak						

	Visina montažne pločice				
	0	2	3	3.5	6
x	34.0	33.0	32.0	32.0	30.5
Pozicija(x)					

	Udaljenost čašice					
	3	4	5	6	7	
Preklop vrata	24.0	1.0	2.1	2.1	2.1	2.0
	22.0	1.0	1.6	1.6	1.5	1.5
	21.0	1.0	1.3	1.3	1.3	1.3
	20.0	1.0	1.1	1.1	1.1	1.1
	19.0	1.0	0.9	0.9	0.9	0.9
	18.0	1.0	0.7	0.7	0.7	0.7
	17.0	1.0	0.6	0.6	0.6	0.6
	16.0	1.0	0.6	0.6	0.6	0.6
Minimalni razmak						

	Visina montažne pločice			
	0	2	3	3.5
x	17.0	16.0	15.0	15.0
Pozicija(x)				