

Riepe Release Agent LPZ/II RI 001

Before pre-milling (edgebanding)

COMPOSITION

Mixture of ethanol

APPLICATION

Spray onto the upper and lower edge area of the workpiece. Prevents the adhesion of emerging glue onto the workpiece.

BENEFITS

Low consumption: <1 litre per fine nozzle per 5000 running metres
Compatible with all commercially available edge bands and adhesives
Finish Quality
High-quality raw materials
Not harmful to the environment or health

PHYSICAL AND CHEMICAL CHARACTERISTICS

Parameter	Value
Form	Liquid
Colour	Colourless
Smell	Alcohol-like
Ignition temperature	425 °C (Product is not selfigniting.)
Melting point	- 100 °C
Boiling range	≥ 78 °C
Flash point	~13 °C
Density	~ 0,79 g/cm ³ (at 20 °C)
Values for explosion	Lower 3,5 Vol % Upper 15,0 Vol % Product is not explosive. (formation of explosive air/steam mixtures is possible)
Vapour pressure	59 hPa (at 20 °C)
VOC	96 % volatile organic compounds

AVAILABLE PACKAGING

10 l, 30 l

SAFETY INSTRUCTIONS

- UN number UN 1170
- Transport Class 3 PG II
- Storage Keep container tightly closed. Store in cool, dry and place
- Disposal According to official regulations, or returnable packaging

SHELF LIFE

Unlimited shelf life when stored properly

FURTHER TECHNICAL DATA

Material Safety Data Sheet

All information contained in this publication are based on our current technical knowledge and experiences. For damages resulting from improper use, we assume no liability.