

PLANNING INFORMATION

All dimensions in millimetres

Installation dimensions	Drawer	NL	SKL	MET
$LWS = (LWK - 42) \begin{smallmatrix} +0 \\ -1.5 \end{smallmatrix}$ min. LWS = 138 mm (2D/3D) max. 16 min. 7 min. 38 10 min. 53 max. 13 min. 10 21 LWK	$SKL - NL - 10 \begin{smallmatrix} +0.5 \\ -0.5 \end{smallmatrix}$ min. 4.5 $\begin{smallmatrix} +1.5 \\ -1.5 \end{smallmatrix}$ min. 12 min. 7 37 $MET = NL + 3$	250	240	253
		270	260	273
		300	290	303
		350	340	353
		400	390	403
		450	440	453
		500	490	503
		550	540	553
		600	590	603
		650	640	653
Inset drawer	$SKL = NL - 10 \begin{smallmatrix} +0.5 \\ -0.5 \end{smallmatrix}$ min. 4.5 $\begin{smallmatrix} +1.5 \\ -1.5 \end{smallmatrix}$ min. 12 min. 7 37 max. 14 min. 14 27 $MET = NL + 30$	700	690	703
		750	740	753
Cutting dimensions for synchronisation rod		LWK - 187		

Mounting position for front locking device	Mounting position for adjustment adapter	Position of synchronisation rod						
10 min. 35 HV +3.5 mm 7.5 19 41 SV ±1.5 mm 23 19 min. 69 min. 69 3D 2D	10 7 32 15 32 min. 35 NV +4 mm min. 35 NV +4 mm 15 3D 2D	A 14 <table><tr><th>NL</th><th>A</th></tr><tr><td>250 - 320</td><td>205</td></tr><tr><td>350 - 750</td><td>241</td></tr></table>	NL	A	250 - 320	205	350 - 750	241
NL	A							
250 - 320	205							
350 - 750	241							

Attachment positions for full extension slide
KV 18 9 23 9 10 12 28 37 250 - 320 350 - 450 480 - 520 550 352 288 256 224 192 160 128 32 0 4 MET = NL + 3 40 kg
Euro screw Ø 6,3 x 14 mm Chipboard screws Ø 4 x 16 mm Head diameter 7 mm

LEGEND

HV	Height adjustment	LWK	Inside cabinet width	NV	Tilt adjustment
KB	Cabinet width	LWS	Inside drawer width	SKL	Drawer length
KV	Front edge of cabinet	MET	Minimum installation depth	SV	Lateral adjustment
L	Length	NL	Nominal length		